



Water 2000 carries a wide range of stainless steel multi-cartridge filter housings for high flow filtration and contaminant holding capabilities. The filter housings can accommodate from 1 to 205 cartridges around. These industrial cartridge filter housings provide high-level filtration for a wide range of applications including city water filtration, boiler water supply, RO-pre-treatment, machine tool coolant or other custom facility water filtration processes.

Stainless Steel cartridge filter housings series (AQUAF-SSMCF) is ideal for most industrial/commercial applications. SSMCF housings easily accept PA Cartridges. All wetted surfaces are constructed of SS304 / SS316 / SS316L and are mirror polished, providing excellent corrosion resistance

Markets

AQUAF-SSMCH can be used in a variety of commercial, industrial and specialty applications.

- RO pre-treatment
- Pharmaceutical manufacturers
- Drinking water
- Fluid chemical blending
- Food & beverages
- Milk & Dairy
- Medical and research
- Hospitals & laboratories
- Painting and plating
- Photographic process
- Chemical plants
- Power plants
- Metal workings
- Cosmetics manufacturing
- Humidification
- Ice makers
- Swimming pool
- Farm irrigation
- Deionization filters
- Specialty filters
- Wastewater / Water re-use

Multi-Cartridge Liquid Filter Vessels

Water 2000 offers a full line of heavy duty liquid cartridge filter housings with various opening configuration

General Specifications *

- Available in SS 304, SS 316 (SS316L also available)
- Standard sizes to accommodate flow rates from 2 to 500 GPM
- Heavy duty band clamp closure
- Larger dia / high capacity housing available only in top flanged connection
- Housings available for 10, 20, 30 & 40 inch long cartridge
- Connection choices are BSP Female ports which protect threads during shipping or 150# ANSI flanges,
- Sanitary connection also available
- All housings have fully welded universal base cups to accept DOE (222 Optional)
- All housings have a universal top seal plate for cup/spring or fin style tops
- Housings are rated at 150 PSI inlet pressure at 200°F
- Heavy Duty Support Legs
- 1/2" Drain and 1/4" NPT vent or gauge (alternative porting available)

*Other customized models available on request

Please give us a call on 042 3542039-40 or email us at sales@water2000.com.pk and one of our professional team member will happily demonstrate how we can save your significant cost on any new equipment and greatly improve the performance of any of your other water or wastewater treatment plant.